

Combiflex PU Threaded Sockets

in acc. with DIN ISO 228



Material

- abrasion resistant polyurethane

Applications

- Screwable threaded connectors for Master-PUR L / H / HX

Properties

- lightweight
- high tension-proof and primarily water-tight connection
- reusable and exchangeable
- simple mounting
- abrasion-resistant
- microbe and hydrolysis-resistant
- shock-proof

Temperature Range

- -40°C to +90°C
- peaks to +125°C

Product Variations

DN hose	thread size	length	weight/piece	type	old article no.	new article no.
	inch	mm	kg			
50	2	83	0,16	L	524-050-107	001457
65	2,5	94	0,23	L	524-065-107	001458
75	3	102	0,26	L	524-075-107	001459
100	4	124	0,53	L	524-100-107	001460
125	5	100	0,65	L	524-125-107	/
150	6	109	0,95	L	524-150-107	001461
50	2	83	0,16	H	525-050-107	005508
65	2,5	94	0,23	H	525-065-107	001463
75	3	102	0,26	H	525-075-107	001464
100	4	124	0,53	H	525-100-107	001465
125	5	100	0,65	H	525-125-107	001466
150	6	109	0,95	H	525-150-107	001467
50	2	83	0,16	HX	526-050-107	001468
65	2	83	0,16	HX	526-065-107	001470
75	2,5	94	0,23	HX	526-075-107	001471
100	2,5	94	0,23	HX	526-100-107	001472
125	3	102	0,26	HX	526-125-107	001474
150	3	102	0,26	HX	526-150-107	001475
50	4	124	0,53	Performance	526-050-P07	006943
65	4	124	0,53	Performance	526-065-P07	/
75	5	100	0,65	Performance	526-075-P07	/
100	5	100	0,65	Performance	526-100-P07	001473
125	6	109	0,95	Performance	526-125-P07	/
150	6	109	0,95	Performance	526-150-P07	/

All data refers to a medium and ambient temperature of +20 °C.

* Refers to the inner hose lining

Subject to technical changes and colour deviations.

Available on request

- Available on request in permanently mounted version for watertight, tensile strengthened connections, other DN sizes, coloured.